

Model VCC 50 SK

Construction year 2024



Technical data

No. 265 – VCC 50 SK	
CNC-System	Heidenhain TNC 640
Traverse ranges X/Y/Z	1760 / 750 / 850 [mm]
Power rapid traverse X/Y/Z	40 / 40 / 30 [m/min]
Clamping surface approx.	2400 x 900 mm
Rotary table	prepared for AXA RTA 4
Tilting spindle head	infinitely adjustable +/- 100° / Gr. B
Speed range	up to 9000 [rpm]
Main drive	max. 56 [kW] (with 40% DC)
Spindle torque	356 [Nm] (with 40% DC)
Spindle taper	SK 50, DIN ISO7388-1
Tool changing system	Disc type magazine with 30 tool places
External cooling	Ring with 8 adjustable cooling nozzles
Through spindle coolant	prepared, up to 30 bar
Chip conveyor	prepared
Covering	Working space encapsulation
Colour	light grey / slate grey (RAL 7035 / 7015)
Additional features	<ul style="list-style-type: none"> • recooling system for central cooling of spindle and switchgear cabinet • one hand operating flushing gun • two fluorescent tubes

For more information please contact
Herr J. Roters, phone. +49 2555 87-80

verkauf@axa-maschinenbau.de